

HTA-50V steam sterilizer

This product is a medical equipment which is a steam sterilizer with high pressure

High pressure steam sterilizer is for clinics and hospitals to sterilize a variety of medical and surgical instruments. And we developed noise reduction kit, automated power blocking system, steam check valve, automated door locking system for product competitiveness.

Main Advantages : Class B steam sterilizer

- Stainless steel Horizontal Chamber
- Pre-programmed cycles for instruments, gloves, liquids
- · Bowie-Dick and vacuum test programs
- Automatic regulation of Temperature
- Digital display of temperature and sterilization temperature
- Vacuum pump: sterilization with pre-vacuum
- Integrated printer for sterilization cycles traceability
- · Luminous indicator for cycle starting

- · Safety in case of lack of water
- Adjustable volume water for each mode
- No door opening when performing sterilization cycles
- Possibility to stop the cycle any moment
- · Audible indication at end of the cycle
- Safety against overheating and overpressure
- · Automatic cut of after one hour of no functioning state

Technical Specifications

Machine Dimension 670(W)x720(L)x 500(H) mm Size of Chamber 50 liters Size of chamber Ø 350 x 520 mm Capacity of chamber 50 liters
Size of chamber Ø 350 x 520 mm Capacity of chamber 50 liters
Capacity of chamber 50 liters
Chamber shape & Material Roud shape & stainless steel
Water tank Max 8L (Usage 5.5L)
Power AC 220V, 50 / 60 Hz
Power Consumption 2.7 Kw (Band Heater 0.4Kw +Shield Heater 2.3Kw)
Sterilization Temp & Pressure 121°C (1.0 kg/cm²) -134°C (2.2 kg/cm²)
Vacuum Pump Oil-less Vacuum pump (40L/min)
Sound Level During Operation <75d B (A)
Sterilization Time 1 - 99 +/- 1 (min)
Dry time 1 - 99 +/- 1(cycle)
Vacuum Pressure 550mmHg (international Spec.)
Control system Microprocessor
Dry Type Band Heater + Vacuum Pump
Weight 91kg
Safety valve, Overcurrent Blocking (NFB),Internal & External Overheating Sensor (EGC
Safety functions Chamber Overheating Sensor, Auto Door Lock S/W.

Option & Accessories

Printer	Thermal printer, Printer roll 57 x 30 m , Bluetooth communication
---------	---





